## Ready To Rent Diesel Generators //



**MG 10000 SSK-5** Ready to Rent 10kVA Diesel Generator

When looking for a robust, reliable, good quality 10kVA diesel generator, look no further than our MG 10000 SSK-5.

GPS Telemetry Tracker



Optional extras:

## Road-tow Kit Features

10kVA (230V / 110V) AC Aux Power

Linz alternator

Kubota diesel engine (Stage 5)

HVO (Hydrotreated Vegetable Oil) fuel approved

Exclusive MHM engine protection shutdown system

Emergency stop button

Central lifting eye and front & side fork pockets

Fully bunded base (110%)

Complete with trolley kit + folding handles

| 36 | en | efi | its |  |
|----|----|-----|-----|--|
|    |    |     |     |  |

Plenty of power to meet the demands of small generator hire

Heavy duty and proven reliability

World class performance and watercooled

Suitable to run off either diesel, HVO or a mixture of both fuels

In the case of low fuel, low oil pressure and battery charge failure

A must on any UK site

Flexible and safe lifting on site

To retain all spilt fluids

For nice and easy manoeuvrability, transport and storage

# Specification

#### Performance

| Alternator                                      | Linz   |  | Noise Level     | LWA=89 dBa@            | 7m=64         |
|---|--------|--|-----------------|------------------------|---------------|
| Single Phase Power (110V) 10kVA/ 8kW            |        | -  | Insulation Cla  | SS                     | Н             |
| Single Phase Power (230V) 10kVA/ 8kW            |        |  | Mechanical P    | rotection – IP         | 23            |
| Engine  |        | Fue  | l Consumption   | @ 75% Load (Litres/hou | r) <b>2.8</b> |
| Make  | Kubota | Fue  | l Tank Capacity | (Litres)               | 40            |
| Type D722E (Stage 5)                            |        | Average Runtime (Hours)  |                 |                        |               |
| Fuel Diesel / HVO (HVO = BS EN 15940:2016 Only) |        | @1   | 00% Load        | 11 @ 75% Load          | 14            |
| Number of Cylinders                             | 3      | @5   | 0% Load         | <b>22</b> @ 25% Load   | 44            |
| Power (HP) 17                                   |        | CO2 Per Hour @ 75% Load  |                 | 7.34kg                 |               |
| Engine Speed (RPM)                              | 3000   | Starting System Deepsea 3110 c/w two wir<br>Auto Start/ Stop facilit |                 | wo wire                |               |
| Cooling   | Water  |  |                 | facility               |               |
|   |        |  |                 |                        |               |



#### **Dimensions** (Machine only

| Length: 1220 mm              | Width: 670 mm | Height: <b>840</b> mm          |
|------------------------------|---------------|--------------------------------|
| Dry Weight (No Fuel): 350 kg |               | Wet Weight (Fuel Full): 381 kg |

| Dimensions (Trolley kit with handles folded out) |                      |                                       |  |  |
|--|----------------------|---------------------------------------|--|--|
| Length: 1635 mm                                  | Width: <b>940</b> mm | Height: 980 mm                        |  |  |
| Dry Weight (No Fuel): <b>365</b> kg              |                      | Wet Weight (Fuel Full): <b>396</b> kg |  |  |
| Dimensions (With road-tow kit)                   |                      |                                       |  |  |

| Length: 2650 mm                     | Width: <b>1300</b> mm | Height: <b>1200</b> mm                |  |  |
|-------------------------------------|-----------------------|---------------------------------------|--|--|
| Dry Weight (No Fuel): <b>485</b> kg |                       | Wet Weight (Fuel Full): <b>516</b> kg |  |  |
|                                     |                       |                                       |  |  |


| Socket             | 1ph (230V)            |     | 1ph (110V) |     |
|--------------------|-----------------------|-----|------------|-----|
| Configuration      | 32A                   | 16A | 32A        | 16A |
| MG 10000 SSK-5     | 1                     | 2   | 2          | 1   |
| Hard wire facility | 1ph (230V)            |     | 1ph (110V) |     |
| MG 10000 SSK-5     | <ul> <li>✓</li> </ul> |     | V          |     |

Designed in the UK.

built in Italy

### For more details call MHM TODAY on 0808 168 9099

Email sales@mhm-group.co.uk or visit us at www.mhm-group.co.uk



(in) (O)