

WELFARE

CABIN

READY

# MG-5 10000 Cube (WELFARE)

Welfare Cabin Ready 9.8kVA Diesel Generator

**GPS** Telemetry

Tracker

When looking for robust, reliable, good guality 9.8kVA Welfare Ready Diesel Generator, look no further than our MG-5 10000 Cube (Welfare).

Remote Start/Stop + timer contro

Optional extras:

### Features

Remote Start/Stop

9.8kVA (230V only) AC Aux Power

Mecc Alte alternator

Kubota diesel engine (Stage 5)

HVO (Hydrotreated Vegetable Oil) fuel approved

Emergency stop button

Central lifting eye

Exclusive MHM-Gen engine protection shutdown system

Extremely compact

Welfare cabin ready

	Denents				
	Plenty of power for most welfare cabin applications				
	Heavy duty and proven reliability				
	World class performance, 1500rpm and watercooled				
	Suitable to run off either diesel, HVO or a mixture of both fuels				
	A must on any UK site				
	Flexible and safe lifting on site				
	In the case of low fuel, low oil pressu and battery charge failure				
	Ideal when saving space is important				
	Easy fit plug and play cabin installati				

Water Cooled Extra Supei Silent

## Renefits

re.

Easy fit, plug and play cabin installation

## Specification

#### Performance

Alternator	Iternator Mecc Alte (AVR)		Noise Level		LWA=79 dBa@	7m=54	
Single Phase Power (110V)	Single Phase Power (110V) N/A		Insulation Cla	ass		Н	
Single Phase Power (230V)	ingle Phase Power (230V) 9.8kVA/ 7.8kW		Mechanical F	Protectio	n – IP	23	
Engine		Fue	l Consumption	@ 75%	Load (Litres/hou	ır) <b>1.9</b>	
Make	ake Kubota		Fuel Tank Capacity (Litres)			55	
Type D1105 (Stage 5)			Average Runtime (Hours)				
Fuel <b>Diesel / HVO</b> (HVO = BSE	N 15940:2016 Only)	@1	00% Load	20	@ 75% Load	29	
Number of Cylinders	3	@ 5	50% Load	46	@ 25% Load	92	
Power (HP)	13.7	(02	2 Per Hour @ 7	5% Loa	d	4.98kg	
Engine Speed (RPM) 1500		Control Panel		Dee	Deepsea 3110 c/w two wire		
Cooling	Water	Control Panel			Auto Start/ Stop facility		

MEAM GEN

HVO

FUEL

APPROVED





#### **Dimensions** (Machine only) Length: 1100 mm Width: 790 mm Height: 1000 mm Dry Weight (No Fuel): 425 kg Wet Weight (Fuel Full): 475 kg

Socket Configuration	1ph (230V)				
Socket Configuration	32A				
MG-5 10000 Cube (Welfare)	2				
Hard wire facility	1ph (230V)				
MG-5 10000 Cube (Welfare)	V				

Designed in the UK.

built in Italy

### For more details call MHM TODAY on 0808 168 9099

Email sales@mhm-group.co.uk or visit us at www.mhm-group.co.uk

Picture shown for illustration purposes only. Actual product may differ in appearance. All specifications are subject to change



(in) (O)