

GW 5/225 - PRO

225A Petrol Welder Gen

Our 225A petrol driven welder generator is a true workhorse with its easy manoeuvrability, compact design and large DC and auxiliary power. Thus making it a great one stop tool solution.



Optional Extras



Road-tow
Kit



Remote
Control

All pictures are for illustration purposes only, actual machines supplied may differ in appearance and specification.

Features

- 3kVA (110v) AC Aux Power
5kVA (230v) AC Aux Power
- DC Welding range 40 - 225A
- Honda petrol engine
- Complete with trolley kit
- Switchless AC and DC power

Benefits

- Plenty of power to run a variety of tools on site
- Will burn a 5mm rod
- Featuring low oil level shutdown
- Nice and easy manoeuvrability
- Can be used as a welder, generator or both simultaneously

Specifications

Performance

| | |
|---------------------------|--------------|
| Type | Tekno Proget |
| Welding - amps D.C. | 40 - 225 |
| Open Circuit Voltage - V | 90 |
| Single Phase Power (110v) | 3kVA/ 2.4kW |
| Single Phase Power (230v) | 5kVA/ 4kW |

| | |
|------------------------------|-----|
| Max Welding Rods - mm | 5 |
| Noise Level LWA=96 dBa@7m=71 | |
| Insulation Class | H |
| Mechanical Protection - IP | 23 |
| Remote Control Socket | n/a |

Engine

| | |
|---------------------|--------|
| Make | Honda |
| Type | GX 390 |
| Fuel | Petrol |
| Number of Cylinders | 1 |
| Power - HP | 13 |

| | |
|------------------------------------|--------|
| Engine Speed - rpm | 3000 |
| Cooling | Air |
| Fuel Consumption - Litres/hour | 2 |
| Fuel Tank Capacity - litres | 6.5 |
| Average Runtime @ 75% Load (Hours) | 3.5 |
| Starting System | Recoil |

Dimensions (Machine only)

| | |
|-----------------|----------------|
| Length - 800 mm | Width - 485 mm |
|-----------------|----------------|

| | |
|-----------------|-----------------|
| Height - 500 mm | Weight - 123 Kg |
|-----------------|-----------------|

Dimensions (With trolley kit - handles folded out)

| | |
|------------------|----------------|
| Length - 1210 mm | Width - 740 mm |
|------------------|----------------|

| | |
|-----------------|-----------------|
| Height - 670 mm | Weight - 129 Kg |
|-----------------|-----------------|

Dimensions (With road-tow kit)

| | |
|------------------|-----------------|
| Length - 2415 mm | Width - 1040 mm |
|------------------|-----------------|

| | |
|-----------------|-----------------|
| Height - 870 mm | Weight - 253 Kg |
|-----------------|-----------------|

Socket Configuration

| | 3ph (400V) | | 1ph (230V) | | 1ph (110V) | |
|-----------------------|------------|-----|------------|-----|------------|-----|
| | 32A | 16A | 32A | 16A | 32A | 16A |
| GW 5/225 - PRO | - | - | 1 | - | 1 | - |

